

View Online at <https://aerobasegroup.com/nsn/5950-00-688-3213>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group

Impedance Rating In Ohms:

820.0 single component single secondary and 1200.0 single component single secondary

Frequency Rating:

60.0 hertz single component

Maximum Transformer Power Rating:

3.5 watts single component

Primary To Secondary Turn Ratio:

1 to 35 single component

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

3.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

5.0 milliamperes dc single component single primary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0