

View Online at <https://aerobasegroup.com/nsn/5950-00-688-5740>

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.938 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

4.625 inches

Body Width:

3.000 inches

Body Height:

5.438 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Special Features:

Dcase metal material, primary winding 115 to 230 v rating, secondary windings rated 6.3 v at 1.4 amp, 6.3 v at 4.5 amp, 6.3 v at 4.5 amp, 6.3 v at 45 amp, 6.3 v at 4.5 amp, 207 v at 125 ma, 289 v at 200 ma

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0