

View Online at <https://aerobasegroup.com/nsn/5950-00-688-5851>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.359 inches single mounting facility single center group and 3.391 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.172 inches single mounting facility single center group and 3.204 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 4.437 inches and 4.500 inches

Body Width:

Between 4.250 inches and 4.313 inches

Body Height:

Between 3.625 inches and 3.688 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 2nd secondary

Winding Power Rating:

7.98 volts-amperes single component 2nd secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0