

View Online at <https://aerobasegroup.com/nsn/5950-00-688-6029>

Reliability Indicator:

Not established

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.062 inches

Body Outside Diameter:

2.812 inches

Maximum Operating Temp:

90.0 degrees celsius

End Application:

Stream (std.Tensioned replenishment at sea method); air traffic control central an/tsw-7c; teletype, model 28; helicopter landing system, lamps mk iii; kidd class ddg; ticonderoga cg (47); arleigh burke ddg; spruance dd (963); nimitz cvn

Inclosure Type:

Open

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Winding Operating Current:

1.75 amperes ac single component single primary input and 2.25 amperes dc single component single primary input

Winding Power Rating:

230.0 volts-amperes single component single primary output

Criticality Code Justification:

Feat

Winding Operating Voltage:

120.00 ac volts single component single primary output and 130.00 ac volts single component single primary output

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0