NSN 5950-00-688-6512

Radio Frequency Coil - Page 1 of 2

Reliability Indicator:

Terminal Type And Quantity:

2 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5950-00-688-6512

| Not established |
|--|
| Overall Length: |
| 1.750 inches |
| Turn Quantity: |
| 25 single component single winding |
| Inductance Rating: |
| 4.95 microhenries single component single winding |
| Coil Form Type: |
| Hollow single component |
| Core Construction: |
| Powdered single component |
| Adjustment Device Drive Type: |
| Slotted screw single component |
| Body Length: |
| 0.875 inches |
| Overall Diameter: |
| 0.406 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing single group |
| Rating Method: |
| Winding turns single component single winding and electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Conductor Size: |
| 0.02010 inches american wire gage single component single winding |
| Winding Operating Current: |
| 100.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 1.000 single component single winding |
| Quality Factor: |
| 70 single component single winding |
| Adjustment Method And Quantity: |
| 1 adjustable core single component |
| Thread Series Designator: |
| Unf single group |

NSN 5950-00-688-6512

Radio Frequency Coil - Page 2 of 2



| _ | | | | | |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0