Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-688-6569

| Reliability Indicator:  |
|---|
| Not established   |
| Impedance Rating In Ohms:   |
| 1000.0 single component single secondary  |
| Frequency Rating:   |
|   |
| 250.0 hertz single component and 5.0 kilohertz single component<br>Brimary To Secondary Type Bation |
| Primary To Secondary Turn Ratio:  |
| 1 to 1-19/64 single component   |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component  |
| Body Length:  |
| Between 1.095 inches and 1.155 inches   |
| Body Width:   |
| Between 1.095 inches and 1.155 inches   |
| Body Height:  |
| Between 1.470 inches and 1.530 inches   |
| Distance Between Mounting Facility Centers:   |
| 0.679 inches single mounting facility single center group   |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 2 single group  |
| Mounting Method:  |
| Threaded stud single group  |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Thready Qty Per Inch (tpi):   |
| 32 single group   |
| Thread Size:  |
| 0.138 inches single group   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 5 solder stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A058b0  |
|   |
|   |