

View Online at <https://aerobasegroup.com/nsn/5950-00-688-6990>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.438 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to six phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Core grounded single component and core grounded and brought out to terminal single component and internal shield brought out to terminal single component

Body Length:

Between 2.047 inches and 2.077 inches

Body Width:

Between 2.297 inches and 2.327 inches

Body Height:

Between 3.110 inches and 3.140 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

250.0 milliamperes ac single component 1st secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0