

View Online at <https://aerobasegroup.com/nsn/5950-00-688-7331>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.219 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.750 inches

Body Width:

3.500 inches

Body Height:

5.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

22.0 amperes ac single component 4th secondary

Winding Operating Voltage:

6.40 ac volts single component 3rd secondary

Special Features:

1primary winding; 7secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0