

View Online at <https://aerobasegroup.com/nsn/5950-00-689-1492>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 2.685 inches and 2.695 inches

Body Width:

Between 2.305 inches and 2.315 inches

Body Height:

Between 3.745 inches and 3.755 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

60.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

115.00 ac volts single component all primary

Special Features:

Secondary currents are listed as dc

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0