## NSN 5950-00-689-2783

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-689-2783

View Online at https://aerobasegroup.com/nsn/5950-00-689-2783
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.187 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.187 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
1.625 inches
Body Width:
1.625 inches
Body Height:
2.375 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
500.0 milliamperes ac single component all secondary
Winding Operating Voltage:
16.50 ac volts single component 2nd secondary and 24.00 ac volts single component 2nd secondary
Special Features:
Two primary taps provided to alter output voltages minus I plus 6 and plus 12 pct
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
10 solder stud
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5950-00-689-2783

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0