

View Online at <https://aerobasegroup.com/nsn/5950-00-691-0606>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.130 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

5.000 inches single mounting facility single center group

**Frequency Rating:**

57.0 hertz single component and 63.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to core single component

**Body Length:**

7.000 inches

**Body Width:**

7.375 inches

**Body Height:**

7.120 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Unthreaded hole single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

74.0 milliamperes ac single component single secondary

**Winding Operating Voltage:**

5.16 ac kilovolts single component single secondary and 5.19 ac kilovolts single component single secondary and 5.85 ac kilovolts single component single secondary or 6.48 ac kilovolts single component single secondary and 6.52 ac kilovolts single component single secondary and 6.55 ac kilovolts single component single secondary and 11.70 ac kilovolts single component single secondary

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0