

View Online at <https://aerobasegroup.com/nsn/5950-00-691-0606>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.130 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.000 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

7.000 inches

Body Width:

7.375 inches

Body Height:

7.120 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

74.0 milliamperes ac single component single secondary

Winding Operating Voltage:

5.16 ac kilovolts single component single secondary and 5.19 ac kilovolts single component single secondary and 5.85 ac kilovolts single component single secondary or 6.48 ac kilovolts single component single secondary and 6.52 ac kilovolts single component single secondary and 6.55 ac kilovolts single component single secondary and 11.70 ac kilovolts single component single secondary

Terminal Type And Quantity:

11 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0