

View Online at <https://aerobasegroup.com/nsn/5950-00-699-4980>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches single mounting facility single center group

Mounting Slot Width:

0.500 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.2 kilovolt-ampere single component

Winding Shielding Method:

Internally shielded single component

Body Length:

8.500 inches

Body Width:

4.500 inches

Body Height:

6.125 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

10.0 amperes ac single component single secondary

Winding Operating Voltage:

110.00 ac volts single component single primary and 120.00 ac volts single component single primary

Terminal Type And Quantity:

1 connector, receptacle and 1 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0