Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-701-0025

Reliability Indicator:         Not established         Impedance Rating In Ohms:         9600.0 single component single secondary         Frequency Rating:         600.0 hertz single component         Primary To Secondary Turn Ratio:         1 to 3 single component         Winding Shielding Method:         External inclosure single component         Body Length:         Between 1.250 inches and 1.312 inches         Body Width:         Between 1.250 inches and 1.312 inches         Body Height:         Between 1.625 inches and 1.750 inches         Distance Between Mounting Facility Centers:         1.250 inches single mounting facility single center group         Inclosure Type:         Hermetically sealed         Mounting Facility Quantity:         2 single group         Mounting Method:         Threaded stud single group         Winding Function And Quantity:         1 primary single component and 1 secondary single component         Thread Size:         0.138 inches single group         Winding Operating Current:         100.0 microamperes dc single component single secondary
Impedance Rating In Ohms:9600.0 single component single secondaryFrequency Rating:600.0 hertz single componentPrimary To Secondary Turn Ratio:1 to 3 single componentWinding Shielding Method:External inclosure single componentBody Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding Operating Current:100.0 microamperes dc single component single secondary
9600.0 single component single secondary Frequency Rating: 600.0 hertz single component Primary To Secondary Turn Ratio: 1 to 3 single component Winding Shielding Method: External inclosure single component Body Length: Between 1.250 inches and 1.312 inches Body Width: Between 1.250 inches and 1.312 inches Body Height: Between 1.625 inches and 1.750 inches Distance Between Mounting Facility Centers: 1.250 inches single mounting facility Single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Minding Function And Quantity: 1 primary single component and 1 secondary single component Thready Cty Per Inch (tpi): 32 single group Minding Operating Current: 1.00.0 microamperes dc single component single secondary
Frequency Rating:600.0 hertz single componentPrimary To Secondary Turn Ratio:1 to 3 single componentWinding Shielding Method:External inclosure single componentBody Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMinding Function And Quantity:1 primary single component and 1 secondary single componentThready Cty Per Inch (tpi):32 single groupMinches Single groupMinding Operating Current:100.0 microamperes dc single component single secondary
<ul> <li>600.0 hertz single component</li> <li>Primary To Secondary Turn Ratio: <ol> <li>to 3 single component</li> <li>Winding Shielding Method:</li> <li>External inclosure single component</li> <li>Body Length:</li> <li>Between 1.250 inches and 1.312 inches</li> <li>Body Width:</li> <li>Between 1.250 inches and 1.312 inches</li> <li>Body Height:</li> <li>Between 1.625 inches and 1.750 inches</li> <li>Distance Between Mounting Facility Centers:</li> <li>1.250 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Minding Function And Quantity:</li> <li>1 primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Minding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ol></li></ul>
Primary To Secondary Turn Ratio:1 to 3 single componentWinding Shielding Method:External inclosure single componentBody Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Method:2 single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding Operating Current:100.0 microamperes dc single component single secondary
1 to 3 single component Winding Shielding Method: External inclosure single component Body Length: Between 1.250 inches and 1.312 inches Body Width: Between 1.250 inches and 1.312 inches Body Height: Between 1.625 inches and 1.750 inches Distance Between Mounting Facility Centers: 1.250 inches single mounting facility single center group Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group O.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
Winding Shielding Method:External inclosure single componentBody Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMinding Method:1 primary single component and 1 secondary single componentThready Gty Per Inch (tpi):32 single groupMinding Operating Current:100.0 microamperes dc single component single secondary
External inclosure single componentBody Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMinding Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThread Size:0.138 inches single groupMinding Operating Current:100.0 microamperes dc single component single secondary
Body Length:Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThread Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
Between 1.250 inches and 1.312 inchesBody Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThread Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
Body Width:Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinel Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
Between 1.250 inches and 1.312 inchesBody Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
Body Height:Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinches single groupMinches single groupMinches single groupInteresting States:0.138 inches single groupMinding Operating Current:100.0 microamperes dc single component single secondary
Between 1.625 inches and 1.750 inchesDistance Between Mounting Facility Centers:1.250 inches single mounting facility single center groupInclosure Type:Hermetically sealedMounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupMinding GroupMinding Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
<ul> <li>Distance Between Mounting Facility Centers:</li> <li>1.250 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded stud single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ul>
<ul> <li>1.250 inches single mounting facility single center group</li> <li>Inclosure Type:</li> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded stud single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ul>
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
<ul> <li>Hermetically sealed</li> <li>Mounting Facility Quantity:</li> <li>2 single group</li> <li>Mounting Method:</li> <li>Threaded stud single group</li> <li>Winding Function And Quantity:</li> <li>1 primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ul>
Mounting Facility Quantity:2 single groupMounting Method:Threaded stud single groupWinding Function And Quantity:1 primary single component and 1 secondary single componentThready Qty Per Inch (tpi):32 single groupThread Size:0.138 inches single groupWinding Operating Current:100.0 microamperes dc single component single secondary
2 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 32 single group 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
<ul> <li>Winding Function And Quantity:</li> <li>1 primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ul>
<ol> <li>primary single component and 1 secondary single component</li> <li>Thready Qty Per Inch (tpi):</li> <li>32 single group</li> <li>Thread Size:</li> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ol>
Thready Qty Per Inch (tpi): 32 single group Thread Size: 0.138 inches single group Winding Operating Current: 100.0 microamperes dc single component single secondary
32 single group <b>Thread Size:</b> 0.138 inches single group <b>Winding Operating Current:</b> 100.0 microamperes dc single component single secondary
Thread Size:         0.138 inches single group         Winding Operating Current:         100.0 microamperes dc single component single secondary
<ul> <li>0.138 inches single group</li> <li>Winding Operating Current:</li> <li>100.0 microamperes dc single component single secondary</li> </ul>
Winding Operating Current: 100.0 microamperes dc single component single secondary
100.0 microamperes dc single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 5950-00-701-0025

Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

