

View Online at <https://aerobasegroup.com/nsn/5950-00-701-0063>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.875 inches

Body Width:

4.375 inches

Body Height:

4.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

49.50 ac volts single component 3rd secondary and 51.00 ac volts single component 3rd secondary and 57.00 ac volts single component 3rd secondary and 57.75 ac volts single component 3rd secondary and 62.00 ac volts single component 3rd secondary and 72.00 ac volts single component 3rd secondary and 76.25 ac volts single component 3rd secondary and 77.00 ac volts single component 3rd secondary and 83.00 ac volts single component 3rd secondary and 84.50 ac volts single component 3rd secondary and 134.00 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

29 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A058b0