

View Online at <https://aerobasegroup.com/nsn/5950-00-701-0063>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.750 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

5.875 inches

**Body Width:**

4.375 inches

**Body Height:**

4.750 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Voltage:**

49.50 ac volts single component 3rd secondary and 51.00 ac volts single component 3rd secondary and 57.00 ac volts single component 3rd secondary and 57.75 ac volts single component 3rd secondary and 62.00 ac volts single component 3rd secondary and 72.00 ac volts single component 3rd secondary and 76.25 ac volts single component 3rd secondary and 77.00 ac volts single component 3rd secondary and 83.00 ac volts single component 3rd secondary and 84.50 ac volts single component 3rd secondary and 134.00 ac volts single component 3rd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

29 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

**Fig:**

A058b0