NSN 5950-00-702-1265

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-702-1265

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.031 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.312 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.125 inches single group |
| Frequency Rating: |
| 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to core single component |
| Body Length: |
| 4.156 inches |
| Body Width: |
| 3.562 inches |
| Body Height: |
| 3.375 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Voltage: |
| 270.00 ac volts single component single secondary and 282.00 ac volts single component single secondary and 298.00 ac volts single |
| component single secondary |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |