## NSN 5950-00-702-5469

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-702-5469

Parallel To Length:

Parallel To Width:

| Reliability Indicator:                                    |
|-----------------------------------------------------------|
| Not established                                           |
| Center To Center Distance Between Mounting Facilities     |
| 2.125 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities     |
| 1.750 inches single mounting facility single center group |
| Inductance Type:                                          |
| Fixed                                                     |
| Inductance Rating:                                        |
| 12.00 henry single component single winding               |
| Body Length:                                              |
| 2.750 inches                                              |
| Body Width:                                               |
| 1.750 inches                                              |
| Body Height:                                              |
| 2.812 inches                                              |
| Winding Quantity:                                         |
| 1 single component                                        |
| Inclosure Type:                                           |
| Fully enclosed                                            |
| Mounting Facility Quantity:                               |
| 4 single group                                            |
| Mounting Method:                                          |
| Threaded stud single group                                |
| Rating Method:                                            |
| Electrical single component single winding                |
| Thready Qty Per Inch (tpi):                               |
| 32 single group                                           |
| Thread Size:                                              |
| 0.138 inches single group                                 |
| Winding Operating Current:                                |
| 70.0 milliamperes dc single component single winding      |
| Dc Resistance Rating In Ohms:                             |
| 350.000 single component single winding                   |
| Thread Series Designator:                                 |
| Unc single group                                          |
| Terminal Type And Quantity:                               |
| 2 tab, solder lug                                         |
| Shelf Life:                                               |
| N/a                                                       |

--

**Unit Of Measure:** 

## NSN 5950-00-702-5469

Reactor - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A058b0