## NSN 5950-00-706-8313

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-706-8313

### **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

#### Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

3.500 inches

#### **Body Width:**

3.250 inches

#### **Body Height:**

3.000 inches

## **Maximum Operating Temp:**

85.0 degrees celsius

## Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Threaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 3 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

#### **Winding Operating Current:**

3.0 amperes ac single component 1st secondary

#### **Winding Operating Voltage:**

6.30 ac volts single component 3rd secondary

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

8 tab, solder lug

## Shelf Life:

N/a

# **NSN 5950-00-706-8313**Power Transformer - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A058b0