

View Online at <https://aerobasegroup.com/nsn/5950-00-706-8728>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

Between 3.490 inches and 3.510 inches

Body Width:

Between 2.865 inches and 2.885 inches

Body Height:

Between 4.240 inches and 4.260 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

600.0 milliamperes ac single component all secondary

Winding Operating Voltage:

68.00 ac volts single component 2nd secondary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

30 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0