# NSN 5950-00-707-1382

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-707-1382

# **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.297 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

#### Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:** 

3.062 inches

**Body Width:** 

2.625 inches

**Body Height:** 

3.188 inches

### **Maximum Operating Temp:**

85.0 degrees celsius

# Inclosure Type:

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

#### **Thread Size:**

0.164 inches single group

### **Winding Operating Current:**

100.0 milliamperes ac single component single secondary

### **Winding Operating Voltage:**

624.00 ac volts single component single secondary

# **Thread Series Designator:**

Unc single group

# **Terminal Type And Quantity:**

4 standoff insulator

#### Shelf Life:

N/a

# **NSN 5950-00-707-1382**Power Transformer - Page 2 of 2



	Of			

Demilitarization:

No

Fiig:

A058b0