## NSN 5950-00-707-1399

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-707-1399

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.625 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.125 inches single mounting facility single center group
Frequency Rating:
60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
3.562 inches
Body Width:
3.062 inches
Body Height:
4.875 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 2 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.190 inches single group
Winding Operating Current:
Winding Operating Current: 70.0 milliamperes ac single component 1st secondary
70.0 milliamperes ac single component 1st secondary
70.0 milliamperes ac single component 1st secondary  Winding Operating Voltage:
70.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 6.30 ac volts single component 2nd secondary
70.0 milliamperes ac single component 1st secondary Winding Operating Voltage: 6.30 ac volts single component 2nd secondary Thread Series Designator:
70.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 6.30 ac volts single component 2nd secondary  Thread Series Designator:  Unf single group
70.0 milliamperes ac single component 1st secondary  Winding Operating Voltage: 6.30 ac volts single component 2nd secondary  Thread Series Designator:  Unf single group  Terminal Type And Quantity:

--

**Unit Of Measure:** 

## NSN 5950-00-707-1399

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0