

View Online at <https://aerobasegroup.com/nsn/5950-00-708-8690>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.030 inches single mounting facility single center group

Mounting Hole Diameter:

0.281 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

5.750 inches

Body Width:

4.560 inches

Body Height:

4.560 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

16.3 amperes ac single component single secondary

Winding Operating Voltage:

396.00 ac volts single component single primary and 440.00 ac volts single component single primary and 484.00 ac volts single component single primary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0