## NSN 5950-00-708-9603

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-708-9603

view Online at https://aerobo	asegioup.com/nsn/3930-00-708-9003
Reliability Indicator:	
Not established	
Center To Center Distance	e Between Mounting Facilities Parallel To Length:
5.620 inches single mountir	ng facility single center group
Center To Center Distance	e Between Mounting Facilities Parallel To Width:
4.500 inches single mountir	ng facility single center group
Frequency Rating:	
380.0 hertz single compone	ent and 420.0 hertz single component
nput-output Phase Relation	onship:
Three phase to three phase	single component
Body Length:	
7.536 inches	
Body Width:	
5.776 inches	
Body Height:	
4.200 inches	
nclosure Type:	
Hermetically sealed	
Mounting Facility Quantity	<i>I</i> :
4 single group	
Mounting Method:	
Threaded stud single group	
Winding Function And Qu	antity:
I primary single component	and 2 secondary single component
Thready Qty Per Inch (tpi):	:
18 single group	
Thread Size:	
0.312 inches single group	
Winding Operating Curren	ıt:
5.0 amperes ac single comp	ponent 1st secondary
Winding Operating Voltage	e:
90.00 ac pounds per hour w	et single component 1st secondary
Thread Series Designator:	:
Unc single group	
Terminal Type And Quanti	ity:
11 solder stud	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

## NSN 5950-00-708-9603

Power Transformer - Page 2 of 2

**Fiig:** A058b0

