Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-709-2003

	ity Indicator:
Not esta	blished
Center ⁻	To Center Distance Between Mounting Facilities Parallel To Length
	ches single mounting facility single center group
Center ⁻	To Center Distance Between Mounting Facilities Parallel To Width:
1.000 in	ches single mounting facility single center group
Impeda	nce Rating In Ohms:
90.0 sin	gle component 2nd secondary
Frequer	ncy Rating:
100.0 he	ertz single component and 8.0 kilohertz single component
Maximu	m Transformer Power Rating:
1.0 watts	s single component
Winding	g Shielding Method:
Internal	shield brought out to terminal single component
Body Le	ength:
1.500 in	ches
Body W	lidth:
1.500 in	ches
Body H	eight:
2.000 in	ches
Inclosu	re Туре:
Hermeti	cally sealed
Mountir	ng Facility Quantity:
4 single	group
Mountir	ng Method:
Threade	d hole single group
Winding	g Function And Quantity:
1 primar	y single component and 3 secondary single component
Thready	/ Qty Per Inch (tpi):
32 single	e group
Thread	Size:
0.138 in	ches single group
Thread	Series Designator:
Unc sing	gle group
Termina	al Type And Quantity:
10 wire l	hook
Shelf Li	fe:
N/a	
Unit Of	Measure:
Demilita	arization:
No	

NSN 5950-00-709-2003

Audio Frequency Transformer - Page 2 of 2

Fiig: A058b0

