NSN 5950-00-710-4607

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-710-4607

Reliability Indicator:
Not established
Turn Quantity:
6-1/4 single component single winding
Mounting Hole Diameter:
0.125 inches single group
Inductance Rating:
0.56 henry single component single winding
Coil Form Type:
Hollow single component
Core Construction:
Laminated single component
Adjustment Device Drive Type:
Slotted screw single component
Body Length:
1.250 inches
Body Width:
0.750 inches
Body Height:
1.531 inches
Inclosure Type:
Open
Mounting Facility Quantity:
2 single group
2 single group Mounting Method:
Mounting Method:
Mounting Method: Bracket single group and unthreaded hole single group
Mounting Method: Bracket single group and unthreaded hole single group Rating Method:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding Quality Factor:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding Quality Factor: 50 single component single winding
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity:
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 2 adjustable core single component
Mounting Method: Bracket single group and unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.00795 inches american wire gage single component single winding Winding Operating Current: 2.5 amperes ac single component single winding Dc Resistance Rating In Ohms: 150.000 single component single winding Quality Factor: 50 single component single winding Adjustment Method And Quantity: 2 adjustable core single component Terminal Type And Quantity:

NSN 5950-00-710-4607

Radio Frequency Coil - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0