

View Online at <https://aerobasegroup.com/nsn/5950-00-715-8591>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Mounting Hole Diameter:

0.218 inches single group

Frequency Rating:

50.0 hertz single component and 10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and brought out to terminal single component

Body Length:

Between 4.410 inches and 4.470 inches

Body Width:

Between 3.595 inches and 3.655 inches

Body Height:

Between 4.270 inches and 4.330 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

35.0 milliamperes ac single component single primary

Winding Operating Voltage:

170.00 ac pounds per hour with retaining chain single component single secondary

Terminal Type And Quantity:

6 binding post

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0