

View Online at <https://aerobasegroup.com/nsn/5950-00-723-0105>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.000 inches single mounting facility single center group

**Mounting Slot Width:**

0.190 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure single component

**Body Length:**

2.810 inches

**Body Width:**

2.620 inches

**Body Height:**

2.690 inches

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and slot single group

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Winding Operating Current:**

300.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

76.00 ac pounds per hour wet single component 2nd secondary

**Test Data Document:**

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0