# NSN 5950-00-723-2605

Power Autotransformer Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-723-2605

| R۵ | lial | silit | v In | dic  | ato  | r- |
|----|------|-------|------|------|------|----|
| Νe | ııaı | JIIIL | v II | ıuıu | ·aιυ | Ή. |

Not established

# **Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.875 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches single mounting facility single center group

## Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

## Input-output Phase Relationship:

Three phase to three phase single component

# **Transformer Winding Connection Type:**

Wye-wye

### **Body Length:**

Between 9.490 inches and 9.510 inches

### **Body Width:**

Between 4.677 inches and 4.697 inches

### **Body Height:**

Between 4.740 inches and 4.760 inches

### **Inclosure Type:**

Fully enclosed

# **Winding Function And Quantity:**

1 primary, fixed autotransformer type single component

### **Winding Operating Current:**

5.0 amperes ac single component single primary output

# **Winding Power Rating:**

2.0 k1lovolt-amperes single component single primary output

# **Winding Operating Voltage:**

108.00 ac pounds per hour dry single component single primary and 121.00 ac pounds per hour with retaining chain single component single primary

### **Terminal Type And Quantity:**

12 tab, solder lug

### Shelf Life:

N/a

# **Unit Of Measure:**

### Demilitarization:

No

# Fiig:

A058b0