

View Online at <https://aerobasegroup.com/nsn/5950-00-724-2228>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility single center group

Mounting Hole Diameter:

0.224 inches single group

Frequency Rating:

380.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.125 inches

Body Width:

Between 2.875 inches and 3.000 inches

Body Height:

Between 3.312 inches and 3.500 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

7.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

6.30 ac volts single component 2nd secondary

Special Features:

Internal shield brought out to two separate terminals

Terminal Type And Quantity:

4 tab, solder lug and 9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0