NSN 5950-00-724-2230

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-724-2230

View Online at https://aerobasegroup.com/nsn/5950-00-724-2230
Reliability Indicator:
Not established
Frequency Rating:
47.0 hertz single component and 63.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core single component
Body Length:
1.312 inches
Body Width:
1.312 inches
Body Height:
1.750 inches
Maximum Operating Temp:
105.0 degrees celsius
Distance Between Mounting Facility Centers:
1.250 inches single mounting facility single center group
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thread Size:
0.138 inches single group
Winding Operating Current:
200.0 milliamperes ac single component single secondary
Winding Power Rating:
150.0 milliwatts single component single secondary
Winding Operating Voltage:
7.00 ac volts single component single secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
4 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5950-00-724-2230

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0