## NSN 5950-00-724-2270

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-724-2270

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.125 inches single mounting facility single center group **Frequency Rating:** 47.0 hertz single component and 63.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component **Body Length:** Between 2.625 inches and 2.875 inches **Body Width:** Between 2.250 inches and 2.500 inches **Body Height:** Between 3.624 inches and 4.000 inches **Maximum Operating Temp:** 105.0 degrees celsius Inclosure Type: Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component **Thread Size:** 0.138 inches single group Winding Operating Current: 2.0 amperes ac single component single secondary Winding Operating Voltage: 12.60 ac volts single component single secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 5 tab, solder lug Shelf Life: N/a Unit Of Measure: ---

## NSN 5950-00-724-2270

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

