

View Online at <https://aerobasegroup.com/nsn/5950-00-724-5288>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.438 inches single mounting facility single center group

Overall Height:

5.750 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 3.813 inches and 3.938 inches

Body Width:

Between 3.250 inches and 3.375 inches

Body Height:

Between 5.062 inches and 5.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

3.5 amperes ac single component single secondary

Winding Operating Voltage:

117.00 ac volts single component single secondary

Special Features:

Internal shield brought out to terminal and core grounded and brought out to terminal

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0