## NSN 5950-00-724-5303

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-724-5303

view Offiline at https://acrobasegroup.com/his//0900-00-724-0900
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.938 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.500 inches single mounting facility single center group
Overall Height:
6.343 inches
Mounting Hole Diameter:
0.226 inches single group
Frequency Rating:
380.0 hertz single component and 420.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internal shield grounded to inclosure and core and brought out to terminal single component
Body Length:
4.562 inches
Body Width:
3.562 inches
Body Height:
5.062 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
50.0 amperes ac single component single secondary
Winding Operating Voltage:
6.30 ac pounds per hour wet single component single secondary
Terminal Type And Quantity:
5 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5950-00-724-5303

Power Transformer - Page 2 of 2



Fiig:

A058b0