

View Online at <https://aerobasegroup.com/nsn/5950-00-725-5617>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.015 inches single mounting facility single center group and 4.109 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.265 inches single mounting facility single center group and 3.359 inches single mounting facility single center group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 5.137 inches and 5.187 inches

Body Width:

Between 4.187 inches and 4.437 inches

Body Height:

Between 0.625 inches and 1.000 inches

Maximum Operating Temp:

65.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

200.0 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

320.00 dc volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0