## NSN 5950-00-728-0866

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-728-0866

### **Reliability Indicator:**

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.437 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

#### **Overall Height:**

6.000 inches

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure single component

#### **Body Length:**

**3.938** inches

#### **Body Width:**

3.375 inches

### **Maximum Operating Temp:**

105.0 degrees celsius

### Inclosure Type:

Hermetically sealed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded stud single group

### **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

#### **Thread Size:**

0.190 inches single group

### **Winding Operating Current:**

75.0 milliamperes ac single component 1st secondary

### **Winding Operating Voltage:**

610.00 ac volts single component 2nd secondary

### **Thread Series Designator:**

Unf single group

### **Terminal Type And Quantity:**

6 tab, solder lug

### Shelf Life:

N/a

### **Unit Of Measure:**

--

# NSN 5950-00-728-0866

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0