

View Online at <https://aerobasegroup.com/nsn/5950-00-728-5339>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.203 inches single group

Frequency Rating:

55.0 hertz single component and 480.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.578 inches

Body Width:

3.875 inches

Body Height:

5.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

3 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

3.219 inches single mounting facility single center group

Winding Operating Current:

30.0 milliamperes ac single component 1st secondary

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

5.000 inches single mounting facility single center group

Winding Operating Voltage:

23.60 ac pounds per hour wet single component all secondary

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0