

View Online at <https://aerobasegroup.com/nsn/5950-00-728-5343>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.110 inches single mounting facility single center group and 2.140 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.735 inches single mounting facility single center group and 1.765 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

Between 2.625 inches and 2.750 inches

**Body Width:**

Between 2.250 inches and 2.375 inches

**Body Height:**

Between 3.625 inches and 3.812 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

500.0 milliamperes ac single component single secondary

**Winding Power Rating:**

27.5 volts-amperes single component single secondary

**Winding Operating Voltage:**

55.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

7 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0