Power Autotransformer Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-729-1503

Dummy Terminal Quantity (non-core):
4
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.500 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.500 inches single mounting facility single center group
Mounting Hole Diameter:
0.250 inches single group
Frequency Rating:
50.0 hertz single component and 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
5.188 inches
Body Width:
4.250 inches
Body Height:
4.875 inches
End Application:
Forrestal class cv; nimitz class cvn; supply class aoe; catapult/arresting gear
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Function And Quantity:
1 primary, variable autotransformer type single component
Winding Operating Current:
7.5 amperes ac single component single primary output
Winding Power Rating:
900.0 volts-amperes single component single primary output
Criticality Code Justification:
Feat
Winding Operating Voltage:
120.00 as pounds per hour wet single component single primary input

120.00 ac pounds per hour wet single component single primary input

## **Special Features:**

Weapon system essential

## Terminal Type And Quantity:

3 tab, solder lug



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0