

View Online at <https://aerobasegroup.com/nsn/5950-00-731-1804>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component and three phase to single phase single component

Transformer Winding Connection Type:

Delta-wye

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

Between 6.172 inches and 6.204 inches

Body Width:

Between 6.109 inches and 6.141 inches

Body Height:

Between 8.109 inches and 8.141 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.312 inches single group

Winding Operating Current:

20.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

312.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0