

View Online at <https://aerobasegroup.com/nsn/5950-00-731-1886>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

11.000 inches single mounting facility single center group and 3.120 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

9.500 inches single mounting facility single center group and 3.120 inches single mounting facility single center group

Mounting Hole Diameter:

0.297 inches single group and 0.297 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

10.000 inches

Body Width:

8.750 inches

Body Height:

6.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

11 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

3 primary single component and 3 secondary single component

Winding Operating Current:

242.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

440.00 ac pounds per hour wet single component all primary

Special Features:

Case metal material; o/a height of terminals, 6 0.750 in. And 3 1.500 in.; eight mtg holes, two rows with 2.750 in. Spacing of holes in row, located on bottom, and three holes located on top of case; secondary output will be 1.57 kv w/y connected primary

Terminal Type And Quantity:

9 standoff, threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0