

View Online at <https://aerobasegroup.com/nsn/5950-00-731-1886>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

11.000 inches single mounting facility single center group and 3.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

9.500 inches single mounting facility single center group and 3.120 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.297 inches single group and 0.297 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Length:**

10.000 inches

**Body Width:**

8.750 inches

**Body Height:**

6.000 inches

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

11 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Winding Function And Quantity:**

3 primary single component and 3 secondary single component

**Winding Operating Current:**

242.0 milliamperes ac single component 3rd secondary

**Winding Operating Voltage:**

440.00 ac pounds per hour wet single component all primary

**Special Features:**

Case metal material; o/a height of terminals, 6 0.750 in. And 3 1.500 in.; eight mtg holes, two rows with 2.750 in. Spacing of holes in row, located on bottom, and three holes located on top of case; secondary output will be 1.57 kv w/y connected primary

**Terminal Type And Quantity:**

9 standoff, threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0