

View Online at <https://aerobasegroup.com/nsn/5950-00-732-7977>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

6.875 inches

Body Width:

3.562 inches

Body Height:

5.375 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.190 inches single group

Winding Operating Current:

100.0 milliamperes ac single component single secondary

Winding Operating Voltage:

4560.00 ac volts single component single secondary and 5280.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

21 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0