NSN 5950-00-733-9255

3 solder stud

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-733-9255

| Reliability Indicator: |
|---|
| Not established |
| Turn Quantity: |
| 392 single component single primary |
| Overall Height: |
| 1.250 inches |
| Inductance Rating: |
| 3.30 millihenries single component single primary and 4.00 millihenries single component single primary |
| Frequency Rating: |
| 39.8 kilohertz single component and 42.2 kilohertz single component |
| Coil Form Type: |
| Hollow single component |
| Adjustment Device Drive Type: |
| Slotted screw single component |
| Body Length: |
| 1.125 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing single group |
| Rating Method: |
| Electrical single component single primary and winding turns single component single primary |
| Winding Function And Quantity: |
| 1 primary single component |
| Thready Qty Per Inch (tpi): |
| 28 single group |
| Thread Size: |
| 0.250 inches single group |
| Winding Conductor Size: |
| 0.00631 inches american wire gage single component single primary |
| Adjustment Method And Quantity: |
| 1 adjustable core single component |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |

NSN 5950-00-733-9255

Radio Frequency Transformer - Page 2 of 2



N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0