NSN 5950-00-736-1205

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-736-1205

Reliability Indicator:

Not established

Turn Quantity:

400 single component single primary

Inductance Rating:

3.775 millihenries single component single primary

Frequency Rating:

100.0 kilohertz single component

Coil Form Type:

Hollow single component

Adjustment Device Drive Type:

Slotted screw single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

0.780 inches

Body Outside Diameter:

0.780 inches

Distance Between Mounting Facility Centers:

0.510 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single primary and winding turns single component single primary

Winding Function And Quantity:

1 primary single component

Thready Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Conductor Size:

0.00397 inches american wire gage single component single primary

Adjustment Method And Quantity:

1 adjustable core single component

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 tab, solder lug

NSN 5950-00-736-1205

Radio Frequency Transformer - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0