## NSN 5950-00-737-0443

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-737-0443

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 3.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group **Frequency Rating:** 60.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component Winding Shielding Method: Internal shield grounded to inclosure and core single component **Body Length:** 4.690 inches **Body Width:** 4.000 inches **Body Height:** 6.640 inches Inclosure Type: Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded stud single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Thready Qty Per Inch (tpi): 20 single group **Thread Size:** 0.250 inches single group Winding Operating Voltage: 165.00 ac volts single component single secondary and 192.00 ac volts single component single secondary and 210.00 ac volts single component single secondary and 280.00 ac volts single component single secondary **Thread Series Designator:** Unc single group **Terminal Type And Quantity:** 15 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No

## NSN 5950-00-737-0443

Power Transformer - Page 2 of 2

**Fiig:** A058b0

