# NSN 5950-00-739-7148

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-739-7148

# **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

4.063 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

4.063 inches single mounting facility single center group

#### Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

## **Transformer Winding Connection Type:**

Wye-delta

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core and brought out to terminal single component

#### **Body Length:**

5.063 inches

**Body Width:** 

5.063 inches

## **Body Height:**

7.000 inches

# Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

# **Mounting Method:**

Threaded stud single group

# **Winding Function And Quantity:**

1 primary single component and 2 secondary single component

#### Thready Qty Per Inch (tpi):

20 single group

#### **Thread Size:**

0.250 inches single group

## **Winding Operating Current:**

60.0 amperes dc single component all secondary

## **Winding Power Rating:**

500.0 milliwatts single component single primary

# **Winding Operating Voltage:**

203.00 ac volts single component single primary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

11 standoff, threaded stud

# NSN 5950-00-739-7148

Power Transformer - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0