

View Online at <https://aerobasegroup.com/nsn/5950-00-740-1298>

Reliability Indicator:

Not established

Mounting Slot Width:

0.190 inches single group

Frequency Rating:

57.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.810 inches

Body Width:

2.620 inches

Body Height:

2.810 inches

Distance Between Mounting Facility Centers:

2.620 inches single mounting facility single center group and 2.120 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

550.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

2.00 ac volts single component 2nd secondary or 17.50 ac volts single component 2nd secondary or 18.50 ac volts single component 2nd secondary or 60.50 ac volts single component 2nd secondary or 61.50 ac volts single component 2nd secondary or 77.00 ac volts single component 2nd secondary or 79.00 ac volts single component 2nd secondary

Terminal Type And Quantity:

14 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0