NSN 5950-00-740-2496

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-740-2496

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.374 inches single mounting facility single center group

Overall Height:

Between 3.095 inches and 3.406 inches

Frequency Rating:

150.0 hertz single component and 360.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 1.812 inches and 1.937 inches

Body Width:

Between 1.687 inches and 1.812 inches

Body Height:

Between 2.563 inches and 2.750 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component single secondary

Winding Operating Voltage:

26.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

Shelf Life:

N/a

NSN 5950-00-740-2496

Power Transformer - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A058b0