NSN 5950-00-751-1251

Reactor - Page 1 of 2

Reliability Indicator:

2 tab, solder lug



View Online at https://aerobasegroup.com/nsn/5950-00-751-1251

| Not established |
|---|
| Overall Length: |
| 0.859 inches |
| Overall Height: |
| 0.978 inches |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 100.00 millihenries single component single winding |
| Frequency Rating: |
| 1.4 kilohertz single component |
| Body Length: |
| 2.313 inches |
| Body Width: |
| 1.219 inches |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Distance Between Mounting Facility Centers: |
| 1.938 inches single mounting facility single center group |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Thready Qty Per Inch (tpi): |
| 40 single group |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 540.0 milliamperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 13.000 single component single winding |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |

NSN 5950-00-751-1251

Reactor - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0